



Mobile Safety Ladder Specification Sheet

Ladder code	Steps	Top step Height	Overall height	Base Width	Base length	Max load	Step Size	Top Platform size	Top handrailing height
ML2	2	495mm	495mm	650mm	550mm	150kg's	175mm x 600mm	175mm x 600mm	n/a
MLH3	3	720mm	1540mm	650mm	800mm	150kg's	175mm x 600mm	350mm x 600mm	825mm
MLH4	4	980mm	1805mm	650mm	950mm	150kg's	175mm x 600mm	350mm x 600mm	825mm
MLH6	6	1520mm	2340mm	950mm	1230mm	150kg's	175mm x 600mm	350mm x 600mm	825mm
MLH8	8	2030mm	2854mm	950mm	1560mm	150kg's	175mm x 600mm	350mm x 600mm	825mm
MLH10	10	2540mm	3370mm	950mm	1920mm	150kg's	175mm x 600mm	350mm x 600mm	825mm
MLH12	12	3050mm	3876mm	950mm	2350mm	150kg's	175mm x 600mm	350mm x 600mm	825mm
MLH15	15	3815mm	4640mm	950mm	2800mm	150kg's	175mm x 600mm	350mm x 600mm	825mm

<u>Finish</u>	Zinc blue, electroplated finish unless otherwise specified
<u>Castors</u>	2x 100mm Swivel/Brake, 2x 100mm Fixed (Except for ML2 which uses 80mm)
<u>Assembly</u>	M8x20/M8x25 Set screw + nyloc nuts
<u>Construction</u>	25x2mm HR Tubing 30x30x5mm Angle iron 30x5mm Flat bar 5mm Laser cut components 1.6mm HR Punched & formed steps (Non-slip) All material mild steel Welded construction, in component form

<u>Safety</u>	Use intended for 1x person + handtools Max load capacity 150kg's (Independently tested to 250kg's UDL) Full handrailing for all steps above 1200mm Lockable castors to be engaged prior to ladder usage
----------------------	--